



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

## **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1. Product identifier**

AP 1 L

### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

#### **Use of the substance/preparation**

Industrial uses: Pad printing auxiliary

#### **Uses advised against**

Use by consumers (private households), as the necessary technical measures and personal protective equipment are not available to private households.

### **1.3. Details of the supplier of the safety data sheet**

#### **Address/Manufacturer**

Marabu GmbH & Co. KG

Asperger Strasse 4

71732 Tamm

Germany

Telephone no. +49-7141/691-0

Information provided Department product safety

by / telephone

E-mail address of PRSI@marabu.com

person responsible

for this SDS

### **1.4. Emergency telephone number**

(+49) (0)621-60-43333

## **SECTION 2: Hazards identification**

### **2.1. Classification of the substance or mixture**

#### **Classification (Regulation (EC) No. 1272/2008)**

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226

STOT SE 3 H335

STOT SE 3 H336

Aquatic Chronic 2 H411

### **2.2. Label elements**

#### **Labelling according to regulation (EC) No 1272/2008**

#### **Hazard pictograms**



#### **Signal word**

Warning

#### **Hazard statements**

H226

Flammable liquid and vapour.



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P261.9 Avoid breathing vapours/spray.  
 P273 Avoid release to the environment.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P312 Call a POISON CENTRE or doctor if you feel unwell.  
 P391 Collect spillage.

**Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)**

contains Hydrocarbons, C9, aromatic; Xylene

**Supplemental information**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3. Other hazards**

No special hazards have to be mentioned.

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Hazardous ingredients****Hydrocarbons, C9, aromatic**

CAS No.	64742-95-6			
EINECS no.	918-668-5			
Registration no.	01-2119455851-35			
Concentration	>= 50	<	100	%
Classification (Regulation (EC) No. 1272/2008)				
	Flam. Liq. 2		H226	
	STOT SE 3		H336	
	STOT SE 3		H335	
	Asp. Tox. 1		H304	
	Aquatic Chronic 2		H411	

**Polyaminoamidsalt (72243/00/2008.0023, Germany)**

Concentration	>= 1	<	5,1	%
Classification (Regulation (EC) No. 1272/2008)				
	Skin Irrit. 2		H315	

**Xylene**

CAS No.	1330-20-7			
EINECS no.	215-535-7			
Registration no.	01-2119488216-32/01-2119486136-34			
Concentration	>= 1	<	4,8	%
Classification (Regulation (EC) No. 1272/2008)				
	Skin Irrit. 2		H315	
	Flam. Liq. 3		H226	
	Acute Tox. 4		H332	
	Acute Tox. 4		H312	
	Eye Irrit. 2		H319	



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

cATpE	inhalative, Dust/Mist	1,5	mg/l
-------	-----------------------	-----	------

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### **After inhalation**

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### **After skin contact**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

#### **After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

#### **After ingestion**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### **Adhere to personal protective measures when giving first aid**

Use personal protective equipment in case of possible contact with the product (see section 8).

### **4.2. Most important symptoms and effects, both acute and delayed**

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Further symptoms are possible.

### **4.3. Indication of any immediate medical attention and special treatment needed**

#### **Hints for the physician / treatment**

Treat symptomatically

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

#### **Non suitable extinguishing media**

water jet

### **5.2. Special hazards arising from the substance or mixture**

In the event of fire the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO); dense black smoke; Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

### **5.3. Advice for firefighters**

#### **Special protective equipment for fire-fighting**

Use self-contained breathing apparatus. Wear full chemical protective clothing. Fire fighter's clothing must conform to European standard EN469.



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

### Other information

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel: Keep away sources of ignition. Remove persons to safety. Ensure adequate ventilation. Keep away unprotected persons. Avoid contact with skin, eyes and clothing. Avoid breathing vapours. For emergency responders: Wear personal protective equipment. Use breathing apparatus if exposed to vapours/dust/aerosol.

### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

### **6.4. Reference to other sections**

Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

#### **Advice on protection against fire and explosion**

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

#### **Classification of fires / temperature class / Ignition group / Dust explosion class**

Classification of fires	B (Combustible liquid substances)
Temperature class	T2

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Requirements for storage rooms and vessels**

Store in accordance with national regulation

#### **Hints on storage assembly**

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### **Further information on storage conditions**

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

sources of heat and direct sunlight. If the storage conditions are not observed, the minimum shelf life is no longer guaranteed. Due to the organic solvents' content of the mixture: Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**7.3. Specific end use(s)**

Pad printing auxiliary

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Exposure limit values**

**Mesitylene**

List	EH40			
Type	WEL			
Value	125	mg/m <sup>3</sup>	25	ppm(V)
Status:	2011			

**Mesitylene**

List	EU			
Value	100	mg/m <sup>3</sup>	20	ppm(V)
Remarks:	2000/39/EG			

**1,2,4-Trimethylbenzene**

List	EH40			
Type	WEL			
Value	125	mg/m <sup>3</sup>	25	ppm(V)
Status:	2011			

**1,2,4-Trimethylbenzene**

List	EU			
Value	100	mg/m <sup>3</sup>	20	ppm(V)
Remarks:	2000/39/EG			

**Xylene**

List	EH40			
Type	WEL			
Value	220	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	441	mg/m <sup>3</sup>	100	ppm(V)
Skin resorption / sensibilisation:	Sk: 2005			

**Xylene**

List	EU			
Value	221	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	442	mg/m <sup>3</sup>	100	ppm(V)
Skin resorption / sensibilisation:	Skin; Remarks: 2000/39/EG			

**Derived No/Minimal Effect Levels (DNEL/DMEL)**

**Xylene**

Type of value	Derived No Effect Level (DNEL)		
Reference group	Worker		
Duration of exposure	Long term		
Route of exposure	inhalative		
Mode of action	Systemic effects		
Concentration	221		mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)		
Reference group	Worker		
Duration of exposure	Short term		
Route of exposure	inhalative		
Mode of action	Systemic effects		

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

Concentration	442	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	221	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	442	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	212	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	65,3	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	260	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	65,3	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	260	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	125	mg/kg/d

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	12,5	mg/kg/d

**Hydrocarbons, C9, aromatic**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	150	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	25	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	32	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	11	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	11	mg/kg/d

**Predicted No Effect Concentration (PNEC)**

**Xylene**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,327	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,327	mg/l

Type of value	PNEC	
Type	Freshwater sediment	
Concentration	12,46	mg/kg



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

Type of value	PNEC	
Type	Marine sediment	
Concentration	12,46	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	2,31	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	6,58	mg/l
Type of value	PNEC	
Type	Water (intermittent release)	
Concentration	0,327	mg/l

## 8.2. Exposure controls

### Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### General protective and hygiene measures

Observe the usual precautions for handling chemicals. Wearing closed work clothing is required. Wash hands and / or face before breaks and after work. Take off dirty, soaked clothes immediately. Wash soiled clothing before re-use. Store work clothing separately.

### Respiratory protection

If workers could be exposed to concentrations above the exposure limit they should use a respirator to EN 140, fitted with a filter suitable for both particulates and vapours, to EN 14387, with an assigned protection factor of at least 10 (e.g. A2P3) . Selection of any respiratory protective equipment should ensure that it is adequate to reduce exposure to protect the worker's health and is suitable for the wearer, task and environment, including consideration of the facial features of the wearer.

### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

Use gloves tested according to EN 374.

For prolonged or repeated handling, use

Appropriate Material	Butyl rubber
Material thickness	> 0,7 mm
Breakthrough time	> 480 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

### Eye protection

Use safety eyewear tested according to EN 166 designed to protect against splash of liquids.

### Body protection

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre. Cotton or cotton/synthetic overalls or coveralls are normally suitable.



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

**Environmental exposure controls**

Do not allow to enter drains or water courses. If the legally prescribed emission limits are exceeded, a suitable exhaust air purification system must be installed.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	liquid		
<b>Colour</b>	colourless		
<b>Odour</b>	solvent-like		
<b>Melting point</b>			
Remarks	Not applicable due to nature of the product		
<b>Freezing point</b>			
Remarks	Not applicable due to nature of the product		
<b>Boiling point or initial boiling point and boiling range</b>			
Reference substance	Hydrocarbons, C9, aromatic		
Value	appr. 140		°C
Pressure	1.013	hPa	
Source	Literature value		
<b>Flammability</b>			
Flammable.			
<b>Upper and lower explosive limits</b>			
Reference substance	Hydrocarbons, C9, aromatic		
Lower explosion limit	appr. 0,7		%(V)
Reference substance	Hydrocarbons, C9, aromatic		
Upper explosion limit	appr. 7		%(V)
Source	Literature value		
<b>Flash point</b>			
Value	46		°C
Method	ASTM D 6450 (CCCFP)		
<b>Auto-ignition temperature</b>			
Value	appr. 400		°C
Source	Literature value		
<b>Decomposition temperature</b>			
Remarks	No decomposition if used as prescribed.		
<b>pH value</b>			
Remarks	Not applicable		
Remarks	substance/mixture is non-soluble (in water)		
<b>Viscosity</b>			
<b>kinematic</b>			
Value	> 1500		mm <sup>2</sup> /s
Temperature	20	°C	
Method	derived from dynamic viscosity		
<b>Solubility(ies)</b>			
Remarks	Not applicable due to nature of the product		
<b>Partition coefficient n-octanol/water (log value)</b>			
Remarks	Not applicable due to nature of the product		
<b>Vapour pressure</b>			
Value	2,12		hPa
Temperature	20	°C	



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

Method calculated

**Density and/or relative density**

Value	0,900	g/cm <sup>3</sup>
Temperature	20 °C	
Method	DIN EN ISO 2811	

**Relative vapour density**

Value	> 1
Source	Literature value

**Particle characteristics**

Remarks	Not applicable due to nature of the product
---------	---

**9.2. Other information****Other information**

The physical specifications are approximate values and refer to the used safety relevant component(s).

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

**10.2. Chemical stability**

Stable under recommended storage and handling conditions (see section 7).

**10.3. Possibility of hazardous reactions**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.4. Conditions to avoid**

Protect from heat/overheating. When exposed to high temperatures may produce hazardous decomposition products. Avoid high concentrations of solvent vapours. Observe the notes on ventilation (section 8).

**10.5. Incompatible materials**

Oxidising agents, strongly alkaline substances, Strongly acidic substances

**10.6. Hazardous decomposition products**

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture). No decomposition during or intended use (see section 1).

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity**

Remarks	Based on available data, the classification criteria are not met.
---------	---

**Acute dermal toxicity**

Remarks	Based on available data, the classification criteria are not met.
---------	---

**Acute dermal toxicity (Components)****Xylene**

Species	rabbit	
LD50	> 4200	mg/kg

**Acute inhalational toxicity**

ATE	> 5	mg/l
-----	-----	------

Administration/Form	Dust/Mist
---------------------	-----------

Method	calculated value (Regulation (EC) No. 1272/2008)
--------	--

Remarks	Based on available data, the classification criteria are not met.
---------	---



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

### Acute inhalative toxicity (Components)

#### Xylene

Species	rat			
LC50	>	29		mg/l
Duration of exposure		4	h	
Administration/Form	Vapors			

#### Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation

Remarks Based on available data, the classification criteria are not met.

#### Sensitization

Remarks Based on available data, the classification criteria are not met.

#### Mutagenicity

Remarks Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

#### Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

### Specific Target Organ Toxicity (STOT)

#### Single exposure

Remarks The classification criteria are met.  
evaluation May cause respiratory irritation.  
evaluation May cause drowsiness or dizziness.

#### Repeated exposure

Remarks Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2 Information on other hazards

### Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

### Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Other information

There are no data available on the mixture itself.  
The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

## SECTION 12: Ecological information



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

## 12.1. Toxicity

### General information

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

## 12.2. Persistence and degradability

### General information

No data available

## 12.3. Bioaccumulative potential

### General information

There are no data available on the mixture itself.

### Partition coefficient n-octanol/water (log value)

Remarks Not applicable due to nature of the product

## 12.4. Mobility in soil

### General information

There are no data available on the mixture itself.

## 12.5. Results of PBT and vPvB assessment

### General information

There are no data available on the mixture itself.

### Results of PBT and vPvB assessment

The product contains no PBT substances  
The product contains no vPvB substances.

## 12.6 Endocrine disrupting properties

### Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## 12.7. Other adverse effects

### General information

There are no data available on the mixture itself.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 03 12\* waste ink containing dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

#### Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.



Trade name: AP 1 L

Version: 10 / GB







Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

## SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1210	1210	1210
14.2. UN proper shipping name	PRINTING INK RELATED MATERIAL	PRINTING INK RELATED MATERIAL	PRINTING INK RELATED MATERIAL
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	III	III	III
Remarks	This product can be transported without the Environmentally Hazardous Substance / Marine Pollutant mark, if packaged in accordance with ADR / IMDG SP375 resp. and transported in sizes of <=5L or <=5Kg.	The product can be transported in accordance with IMDG Code paragraph 2.10.2.7, provided packaging not more than 5 l / 5 kg.	The product is not subject to any other provisions of IATA provided packaging of not more than 5 l / 5 kg (A197)
Limited Quantity	5 l	5 l	
Transport category	3		
14.5. Environmental hazards	 ENVIRONMENTALLY HAZARDOUS	Marine Pollutant 	 ENVIRONMENTALLY HAZARDOUS

### Information for all modes of transport

#### 14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

### Other information

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Major-accident categories acc. 96/82/EC



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

Category	9.II	Dangerous for environment	200.000	kg	500.000	kg
Category	6	Flammable	5.000.000	kg	50.000.000	kg

**VOC**

VOC (EU)	87,44	%	
VOC (EU)	787	g/l	

**Other regulations, restrictions and prohibition regulations**

The product complies with the requirements of the Persistent Organic Pollutants Regulation 2019/1021.  
 The product complies with the requirements of Regulation 1005/2009 on substances that deplete the ozone layer.  
 The product is not subject to Regulation 649/2012 on the export and import of dangerous chemicals.

**Other information**

The product does not contain substances of very high concern (SVHC).

**Other information**

- All components are contained in the TSCA inventory or exempted.
- All components are contained in the PICCS inventory.
- All components are contained in the DSL inventory.
- All components are contained in the IECSC inventory.
- All components are contained in the ECL inventory.
- All components are contained in the AICS inventory.
- All components are contained in the NZIOC inventory.
- All components are contained in the ENCS inventory.

**15.2. Chemical safety assessment**

For this preparation a chemical safety assessment has not been carried out.

**SECTION 16: Other information**

**Hazard statements listed in Chapter 3**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**CLP categories listed in Chapter 3**

Acute Tox. 4	Acute toxicity, Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 2	Flammable liquid, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Skin Irrit. 2	Skin irritation, Category 2
STOT RE 2	Specific target organ toxicity - repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

**Supplemental information**

Relevant changes compared with the previous version of the safety data sheet are marked with: \*\*\*  
 This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.  
 The information in this Safety Data Sheet is based on the present state of knowledge and current

**Safety data sheet in accordance with regulation (EC) No 1907/2006**



Trade name: AP 1 L

Version: 10 / GB

Date revised: 13.10.2023

Substance number: 3505005700074

Replaces Version: 9 / GB

Print date: 15.10.23

legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.