



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

## **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1. Product identifier**

UR 3 5 L

### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

#### **Use of the substance/preparation**

Cleaner for screen and pad printing

#### **Identified Uses**

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
PROC1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
PROC2	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC4	Chemical production where opportunity for exposure arises
PROC5	Mixing or blending in batch processes
PROC8a	Transfer of substance or mixture (charging and discharging) at nondedicated facilities
PROC8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC10	Roller application or brushing
PROC11	Non industrial spraying
PROC13	Treatment of articles by dipping and pouring
PROC19	Manual activities involving hand contact
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8d	Wide dispersive outdoor use of processing aids in open systems

#### **Uses advised against**

SU21 Consumer uses: Private households (= general public = consumers)

### **1.3. Details of the supplier of the safety data sheet**

#### **Address/Manufacturer**

Marabu GmbH & Co. KG  
 Asperger Strasse 4  
 71732 Tamm  
 Germany  
 Telephone no. +49-7141/691-0  
 Fax no. +49-7141/691-147  
 Information provided by / telephone Department product safety  
 E-mail address of person responsible for this SDS PRSI@marabu.com

### **1.4. Emergency telephone number**

(+49) (0)621-60-43333

## **SECTION 2: Hazards identification \*\*\***

### **2.1. Classification of the substance or mixture**

Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

**Classification (Regulation (EC) No. 1272/2008)**

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
Eye Irrit. 2	H319
Repr. 2	H361fd
STOT SE 3	H335
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

**2.2. Label elements****Labelling according to regulation (EC) No 1272/2008****Hazard pictograms****Signal word**

Danger

**Hazard statements \*\*\***

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H304	May be fatal if swallowed and enters airways.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary statements \*\*\***

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261.9	Avoid breathing vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P331	Do NOT induce vomiting.

**Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)**

contains	Solvent naphtha (petroleum), light arom. n-Butyl acetate; 4-Hydroxy-4-methylpentan-2-one
----------	---

**Supplemental information**

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

**2.3. Other hazards**

No special hazards have to be mentioned.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Solvent mixture of aromatic hydrocarbons (C9-C10), esters and ketones



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

### Hazardous ingredients

#### Solvent naphtha (petroleum), light arom.

CAS No.	64742-95-6
EINECS no.	265-199-0
Registration no.	01-2119455851-35 (LIST NUMBER 918-668-5)
Concentration	>= 50 < 100 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
STOT SE 3	H336
STOT SE 3	H335
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

#### 4-Hydroxy-4-methylpentan-2-one

CAS No.	123-42-2
EINECS no.	204-626-7
Registration no.	01-2119473975-21
Concentration	>= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
Eye Irrit. 2	H319
STOT SE 3	H335
Repr. 2	H361fd

Concentration limits (Regulation (EC) No. 1272/2008)

Eye Irrit. 2	H319	>= 10
--------------	------	-------

#### n-Butyl acetate

CAS No.	123-86-4
EINECS no.	204-658-1
Registration no.	01-2119485493-29
Concentration	>= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
STOT SE 3	H336

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

#### **After ingestion**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Until now no symptoms known so far.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

##### **Hints for the physician / treatment**

Treat symptomatically

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

##### **Non suitable extinguishing media**

Not be used for safety reasons: water jet

#### **5.2. Special hazards arising from the substance or mixture**

In the event of fire the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO); dense black smoke

#### **5.3. Advice for firefighters**

##### **Special protective equipment for fire-fighting**

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

#### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

#### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

#### **6.4. Reference to other sections**

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

### Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires	B (Combustible liquid substances)
Temperature class	T2

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation

### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

### Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

## 7.3. Specific end use(s)

Cleaner for screen and pad printing

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limit values

##### 4-Hydroxy-4-methylpentan-2-one

List	EH40			
Type	WEL			
Value	241	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	362	mg/m <sup>3</sup>	75	ppm(V)
Status: 2011				

##### n-Butyl acetate

List	EH40			
Type	WEL			
Value	724	mg/m <sup>3</sup>	150	ppm(V)
Short term exposure limit	966	mg/m <sup>3</sup>	200	ppm(V)
Status: 2011				

##### Mesitylene

List	EH40			
Type	WEL			
Value	125	mg/m <sup>3</sup>	25	ppm(V)
Status: 2011				

##### 1,2,4-Trimethylbenzene

List	EH40			
Type	WEL			
Value	125	mg/m <sup>3</sup>	25	ppm(V)



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

Status: 2011

**Derived No/Minimal Effect Levels (DNEL/DMEL)**

**4-Hydroxy-4-methylpentan-2-one**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	240	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	32,6	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	467	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	5,8	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	1,67	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	33	mg/kg/d

**n-Butyl acetate**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	600	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	

Safety data sheet in accordance with regulation (EC) No 1907/2006



Marabu

Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

Mode of action	Local effects	
Concentration	600	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	35,7	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	35,7	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	11	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	11	mg/kg/d



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long term  
 Route of exposure dermal  
 Mode of action Systemic effects  
 Concentration 6 mg/kg/d

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Short term  
 Route of exposure dermal  
 Mode of action Systemic effects  
 Concentration 6 mg/kg/d

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long term  
 Route of exposure oral  
 Mode of action Systemic effects  
 Concentration 2 mg/kg/d

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Short term  
 Route of exposure oral  
 Mode of action Systemic effects  
 Concentration 2 mg/kg/d

**Solvent naphtha (petroleum), light arom.**

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long term  
 Route of exposure oral  
 Mode of action Systemic effects  
 Concentration 11 mg/kg

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long term  
 Route of exposure dermal  
 Mode of action Systemic effects  
 Concentration 11 mg/kg

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long term  
 Route of exposure inhalative  
 Mode of action Systemic effects  
 Concentration 32 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)  
 Reference group Worker  
 Duration of exposure Long term  
 Route of exposure inhalative  
 Mode of action Systemic effects  
 Concentration 150 mg/m<sup>3</sup>



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	25	mg/kg/d

**Predicted No Effect Concentration (PNEC)**

**4-Hydroxy-4-methylpentan-2-one**

Type of value	PNEC	
Type	Freshwater	
Concentration	2	mg/kg
Type of value	PNEC	
Type	Saltwater	
Concentration	0,2	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	100	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	7,4	mg/kg/d
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,74	mg/kg/d
Type of value	PNEC	
Type	Soil	
Concentration	0,3	mg/kg/d

**n-Butyl acetate**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,18	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,018	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,981	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,0981	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,0903	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

Concentration	35,6	mg/l
Type of value	PNEC	
Type	Water (intermittent release)	
Concentration	0,36	mg/l

## 8.2. Exposure controls

### Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm

Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

### Eye protection

Use safety eyewear designed to protect against splash of liquids.

### Body protection

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Form</b>	Liquid
<b>Colour</b>	colourless, clear
<b>Odour</b>	solvent-like
<b>Odour threshold</b>	
Remarks	No data available
<b>pH value</b>	
Remarks	Not applicable
<b>Melting point</b>	
Remarks	not determined
<b>Freezing point</b>	
Remarks	not determined
<b>Initial boiling point and boiling range</b>	
Value	appr. 124 °C
Pressure	1.013 hPa



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

Source Literature value

**Flash point**

Value 42 °C

Method ASTM D 6450 (CCCFP)

**Evaporation rate (ether = 1) :**

Remarks not determined

**Flammability (solid, gas)**

Not applicable

**Upper/lower flammability or explosive limits**

Lower explosion limit appr. 0,7 %(V)

Upper explosion limit appr. 8 %(V)

Source Literature value

**Vapour pressure**

Value appr. 4 hPa

Temperature 20 °C

Method calculated

**Vapour density**

Remarks not determined

**Density**Value 0,88 g/cm<sup>3</sup>

Temperature 20 °C

Method DIN EN ISO 2811

**Solubility in water**

Remarks partially miscible

**Partition coefficient: n-octanol/water**

Remarks Not applicable

**Ignition temperature**

Value appr. 420 °C

Source Literature value

**Efflux time**

Value &lt; 12 s

Method DIN 53211 4 mm

**Explosive properties**

evaluation no

**Oxidising properties**

evaluation None known

**9.2. Other information****Other information**

The physical specifications are approximate values and refer to the used safety relevant component(s).

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

**10.2. Chemical stability**

Stable under recommended storage and handling conditions (see section 7).

**10.3. Possibility of hazardous reactions**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

exothermic reactions.

**10.4. Conditions to avoid**

When exposed to high temperatures may produce hazardous decomposition products.

**10.5. Incompatible materials**

No hazardous reactions when stored and handled according to prescribed instructions.

**10.6. Hazardous decomposition products**

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute oral toxicity**

Remarks Based on available data, the classification criteria are not met.

**Acute oral toxicity (Components)****4-Hydroxy-4-methylpentan-2-one**

Species	rat		
LD50	3002		mg/kg
Method	OECD 401		

**n-Butyl acetate**

Species	rat (female)		
LD50	10760		mg/kg
Method	OECD 423		

**Acute dermal toxicity**

Remarks Based on available data, the classification criteria are not met.

**Acute dermal toxicity (Components)****4-Hydroxy-4-methylpentan-2-one**

Species	rabbit		
LD50	13500		mg/kg

**n-Butyl acetate**

Species	Rats (male/female)		
LD50	14112		mg/kg
Method	OECD 402		

**Acute inhalational toxicity**

Remarks Based on available data, the classification criteria are not met.

**Acute inhalative toxicity (Components)****4-Hydroxy-4-methylpentan-2-one**

Species	rat		
LD0	7,6		mg/l
Duration of exposure	4	h	
Administration/Form	Vapors		
Method	OECD 403		

**n-Butyl acetate**

Species	Rats (male/female)		
LC50	> 21		mg/l
Duration of exposure	4	h	
Method	OECD 403		

**Skin corrosion/irritation**

Remarks Based on available data, the classification criteria are not met.

**Skin corrosion/irritation (Components)**



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

**4-Hydroxy-4-methylpentan-2-one**

Species rabbit  
 evaluation slight irritant effect - does not require labelling

**Serious eye damage/irritation**

evaluation irritant  
 Remarks The classification criteria are met.

**Serious eye damage/irritation (Components)****4-Hydroxy-4-methylpentan-2-one**

Species rabbit  
 evaluation irritant  
 Method EEC 84/449, B.5

**Sensitization**

Remarks Based on available data, the classification criteria are not met.

**Sensitization (Components)****4-Hydroxy-4-methylpentan-2-one**

Species guinea pig  
 evaluation non-sensitizing  
 Method OECD 406

**Mutagenicity**

Remarks Based on available data, the classification criteria are not met.

**Reproductive toxicity**

evaluation Suspected of damaging fertility. Suspected of damaging the unborn child.  
 Remarks The classification criteria are met.

**Carcinogenicity**

Remarks Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT)****Single exposure**

Remarks The classification criteria are met.  
 evaluation May cause respiratory irritation.  
 evaluation May cause drowsiness or dizziness.

**Repeated exposure**

Remarks Based on available data, the classification criteria are not met.

**Aspiration hazard**

Harmful: may cause lung damage if swallowed.  
 The classification criteria are met.

**Experience in practice**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Other information**

There are no data available on the mixture itself.  
 The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

#### **General information**

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

#### **Fish toxicity (Components)**

##### **Solvent naphtha (petroleum), light arom.**

Species	rainbow trout ( <i>Oncorhynchus mykiss</i> )		
LL50	9,2		mg/l
Duration of exposure	96	h	

##### **4-Hydroxy-4-methylpentan-2-one**

Species	red killifish		
LC50	> 100		mg/l
Duration of exposure	96	h	

##### **4-Hydroxy-4-methylpentan-2-one**

Species	Menicia beryllina		
LC50	420000		µg/l

#### **Daphnia toxicity (Components)**

##### **Solvent naphtha (petroleum), light arom.**

LL0	3,2		mg/l
Duration of exposure	48	h	

##### **4-Hydroxy-4-methylpentan-2-one**

Species	Daphnia magna		
EC50	> 1000		mg/l
Duration of exposure	48	h	

#### **Algae toxicity (Components)**

##### **Solvent naphtha (petroleum), light arom.**

Species	Desmodesmus		
ErC50	0,42		mg/l
Duration of exposure	72	h	

##### **Solvent naphtha (petroleum), light arom.**

Species	Pseudokirchneriella subcapitata		
EC50	0,29		mg/l
Duration of exposure	72	h	
Source	REACH registration dossier		

##### **4-Hydroxy-4-methylpentan-2-one**

Species	Desmodesmus		
ErC50	> 1000		mg/l
Duration of exposure	72	h	

##### **4-Hydroxy-4-methylpentan-2-one**

Species	Desmodesmus		
NOEC	1000		mg/l
Duration of exposure	72	h	

### **12.2. Persistence and degradability**

#### **General information**

No data available

#### **Biodegradability (Components)**

##### **4-Hydroxy-4-methylpentan-2-one**



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

Value	98,51	%
Duration of test evaluation	28	d
	Readily biodegradable (according to OECD criteria)	

### 12.3. Bioaccumulative potential

#### General information

There are no data available on the mixture itself.

#### Partition coefficient: n-octanol/water

Remarks Not applicable

### 12.4. Mobility in soil

#### General information

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

#### General information

There are no data available on the mixture itself.

### 12.6. Other adverse effects

#### General information

There are no data available on the mixture itself.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 03 12\* waste ink containing dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

#### Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

## SECTION 14: Transport information



Trade name: UR 3 5 L







Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT RELATED MATERIAL (Solvent naphtha (petroleum), light arom.)	PAINT RELATED MATERIAL (Solvent naphtha (petroleum), light arom.)	PAINT RELATED MATERIAL (Solvent naphtha (petroleum), light arom.)
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	III	III	III
Special provision	640E		
Limited Quantity	5 I		
Transport category	3		
14.5. Environmental hazards	 ENVIRONMENTALLY HAZARDOUS	Marine Pollutant 	 ENVIRONMENTALLY HAZARDOUS

**Information for all modes of transport**

**14.6. Special precautions for user**

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Other information**

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

no

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Major-accident categories acc. 96/82/EC**

Category	9.II	Dangerous for environment	200.000	kg	500.000	kg
Category	6	Flammable	5.000.000	kg	50.000.000	kg

**VOC**

VOC (EU)	100	%	
VOC (EU)		880	g/l



Trade name: UR 3 5 L

Version: 8 / GB

Date revised: 05.05.2021

Substance number: 3503009800011

Replaces Version: 7 / GB

Print date: 07.05.21

### Other information

The product does not contain substances of very high concern (SVHC).

### Other information

All components are contained in the PICCS inventory.  
 All components are contained in the DSL inventory.  
 All components are contained in the IECSC inventory.  
 All components are contained in the ECL inventory.  
 All components are contained in the TSCA inventory or exempted.  
 All components are contained in the AICS inventory.  
 All components are contained in the NZIOC inventory.  
 All components are contained in the ENCS inventory.

## 15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

## SECTION 16: Other information

### Hazard statements listed in Chapter 3

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.

### CLP categories listed in Chapter 3

Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Repr. 2	Reproductive toxicity, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

### Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: \*\*\*  
 This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.  
 The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.